



## Flow Sensor SS.20.250

Anemometer

The smallest all-rounder  
for universal use and high-performance



Ventilation / air-conditioning  
Cleanroom / pharmaceuticals

D-EN-SS20-250-20190403

- Control and energy-efficient control of fans
- Continuous monitoring of filter units
- Safe control of the volume flow in the case of suction systems
- Monitoring of laminar flow in clean rooms



## Flow Sensor SS.20.250

### Anemometer

#### **For ventilation, air-conditioning, cleanroom and pharmaceutical applications.**

In many applications, direct measurement of the flow velocity and of the volumetric flow in air and gases is the ideal solution. Owing to the high requirements in modern control technology, the flow sensor used must be able to measure precisely and quickly over an extremely wide range from "almost zero" to the maximum value.

#### **Typical applications of the flow sensor SS 20.250 with dumbbell head technology include:**

- Monitoring and energy-efficient controlling of fans
- Continuous monitoring of filter units
- Safe control of the volumetric flow of extraction units
- Monitoring of the laminar flow in cleanrooms

#### **The smallest all-rounder**


Thanks to its compact mechanical design, the SS 20.250 can be installed very easily via a flange or a compression fitting. Its complete electronics are housed in the robust metal sensor tube, which has a diameter of only 9 mm.





## Flow Sensor SS.20.250

### Anemometer



#### Everything in view

Function monitoring by means of an integrated 2-color LED display (green & red) signals the operating state and Assists in quick troubleshooting on site.

#### Everything in flow

The integrated temperature measurement is located behind a metal sleeve in the sensor tube which is inserted into the medium to be measured. This allows fast response to changes in flow and temperature of the media.

#### Everything in its place

The sensor element for the flow measurement is located between the two "dumbbell disks", which ensure an aerodynamic flow line. A resistant plastic coating (PM, black) or Parylene (transparent) is available as an option.

#### Technology

Thanks to the dumbbell technology used and the high flow angle (radial: 360°, axial:  $\pm 45^\circ$ ), the sensor can be positioned in the gas flow safely and quickly. In addition to detecting the standard flow velocity of 0.06 to 20 m / s, it also measures the temperature of the medium. The available linear output signals are 4 ... 20 mA and 0 ... 10 V in each case – as a function of the connected load resistance giving you a universal sensor and automatic detection of U or I output.

#### Protection from dust and aggressive gases

Using the patented dumbbell head also allows measurements to be made in dust-containing gases. If the sensor gets dirty, it can be cleaned again by the user without problems. Upon request the sensor can also be delivered two special protective coatings to increase the resistance against aggressive media such as hydrochloric acid, acetone, sulfuric acid and many more.

#### Measuring accuracy in black and white

Optionally, the flow sensor SS 20.250 can also be delivered with high-precision calibration and ISO calibration certificate, which documents its high precision and reproducibility. You can have this calibration renewed at any time.



## Flow Sensor SS.20.250

### Anemometer

Technical data	
Measurement specific data	
Measurement values	<ul style="list-style-type: none"> <li>Standard velocity <math>W_N</math> based on standard conditions of 20°C and 1,013.25 hPa</li> <li>Temperature of the medium <math>T_M</math></li> </ul>
Medium to be measured	Air or nitrogen, other gases upon request
Measuring range $w_N$	0 ... 1 / 10 / 20 m/s selectable
Lower detection limit $w_N$	0.06 m/s
Measuring range $T_M$	-20 ... +70 °C
Measuring accuracy	
Standard $W_N$ <sup>1)</sup>	± (5 % of measured value + [0.4 % of final value; min. 0.02 m/s])
High precision $W_N$ <sup>1)</sup> (optional)	± (3 % of measured value + [0.4 % of final value; min. 0.02 m/s])
Reproducibility $w_N$	± 1.5 % of measured value
Response time $t_{90}$ $w_N$	3 s (jump from 0 to 5 m/s of air)
Temperature gradient $w_N$	< 2 K/min at 5 m/s
Measurement accuracy $T_M$ (for $w_N > 2$ m/s)	± 1 K (10 ... 30 °C); ± 2 K (remaining measuring range)
Operating temperature	
Sensor and electronics	-20 ... +70 °C
Storage temperature	-30 ... +85 °C

D-EN-SS20-250-20190403



## Flow Sensor SS.20.250

### Anemometer

Technical data	
Material	
Sensor tube	Stainless steel 1.4571
Sensor head	PBT glass fiber reinforced, stainless steel 1.4571
Protective coating (optional)	Polyurethane derivative, Parylene
Connecting cable	PVC, halogen-free
General data	
Medium environment	Non-condensing (up to 95 % RH)
Operating pressure	Atmospheric (700 ... 1,300 hPa)
Display	Dual LED green / red
Supply voltage	24 V AC/DC $\pm$ 10 %
Current consumption	< 60 mA (typical), max. 100 mA
Output signals for temperature and flow Auto U/I	0 ... 10 V / 4 ... 20 mA (short-circuit protected): Voltage output: > 500 $\Omega$ Current output: < 500 $\Omega$ Hysteresis: 50 $\Omega$
Connection	Permanently connected cable, 5-pin, length 2 m or selectable
Admissible cable length	100 m max.
Installation position	Any
Minimum immersion depth	58 mm (< 58 mm upon request)
Ingress protection / protection class	IP 65 / III (SELV) or PELV
Sensor length	300 / 500 mm
Weight	200 g max.

D-EN-SS20-250-20190403



## Flow Sensor SS.20.250

Anemometer

Order information							
	Description	ID-No.					
Basic sensor	SCHMIDT flow sensor SS 20.250; 2x output signal 4... 20 mA / 0 ... 10 V; cable length 2 m	526 340-	X	Y	Z	P	A
	Options						
Mechanical type	Sensor length 300 mm		1				
	Sensor length 500 mm		2				
Measuring ranges and calibration	Measuring range 0 ... 1 m/s			1			
	Measuring range 0 ... 10 m/s			2			
	Measuring range 0 ... 20 m/s			3			
	Standard calibration				1		
	High-precision flow calibration, including ISO calibration certificate				2		
Protection type	Without protecting coating					1	
	With protective coating (PU, black)					2	
	Fully coated (Parylene, transparent)					3	
Connecting cable	Cable length 2 m						1
	Special cable length: _____m (2.5---100 m)						2

D-EN-SS20-250-20190403



## Flow Sensor SS.20.250

Anemometer

Order information		
	Description	ID-No.
Accessories	Mounting flange, steel, galvanic zinc-plated	301 048
	Wall-mounting flange, stainless steel, PTFE- clamping ring	520 181
	Press fitting, stainless steel, G½, atmospheric pressure	532 160
	Press fitting brass, G½ atmospheric pressure	517 206
	Welded sleeve, steel, G½, EN 10241, 5 pcs	524 916
	Welded sleeve, stainless steel, G½, EN10241, 2 pcs	524 882
	Attachable protective clip for dumbbell head against mechanical influences, stainless steel	531 026
	Power supply: output 24 V DC / 1 A; input 115 / 230 V AC	535 282
	LED display MD 10.010 in wall housing to show the volume flow and flow velocity, 85 ... 230 V AC and sensor power supply	527 320
	LED display MD 10.010, similar to 527 320 but with 24 V DC voltage supply	527 330
	LED display MD 10.015, similar to 527 320 but with additional sum function and a second measuring input	527 330
	LED display MD 10.015, similar to 527 330 but with 24 V DC voltage supply	528 250
	Assembly kit for pipe assembly suitable for MD 10.010 / 10.015, including pipe clamps and collar for adjustment to the pipe diameter	531 394

D-EN-SS20-250-20190403